




△ SPECIFICATION


Current Rating:1.0A AC/DC
Voltage Rating:125V AC/DC
Contact Resistance:20 Milliohms Max.
Withstanding Voltage:250V AC/Minute
Insulation Resistance:100 Megaohms Min.
△ Temperature Range:-25°C~+85°C
Insulator:PA46(UL94V-0),Nature
Pin:Phosphor Bronze,Tin Plated Over Nickel
Solder Tab:Brass,Tin Plated Over Nickel
RoHS Compliant




2P,3P





△ Section:A-A



△ 4~15P



Mating Height Drawing



△ Recommended P.C.B. Layout(Top View)
(PCB Board Tolerance±0.05)

Pin	A	B	C
02	1.25	7.25	4.25
03	2.50	8.50	5.50
04	3.75	9.75	6.75
05	5.00	11.00	8.00
06	6.25	12.25	9.25
07	7.50	13.50	10.50
08	8.75	14.75	11.75
09	10.00	16.00	13.00
10	11.25	17.25	14.25
11	12.50	18.50	15.50
12	13.75	19.75	16.75
13	15.00	21.00	18.00
14	16.25	22.25	19.25
15	17.50	23.50	20.50

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No. △

01258

SCALE NONE

APPROVED BY MEI

CHECKED BY HZF

DRAWING BY CYP

REV. A3

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE

△ X. ±0.30
△ XX ±0.25
△ XXX ±0.20
△ ANG. ±1°

UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△3	A3	Modify Data	HZF	07/17/2023
△2	A2	Modify Data	HZF	12/04/2019
△1	A1	Modify Data	HZF	04/17/2019
△0	A0	NEW RELEASE	HZF	12/30/2015