




SPECIFICATION
 Current Rating: 3A AC,DC
 Voltage Rating: 250V AC Max.
 Operating Temperature: -25°C~+85°C
 Insulation Resistance: 1000 Megaohms Min.
 Withstand Voltage: 1000V AC/Minute
 Contact Resistance: 20 Milliohms Max.
 Material: PA66(UL94V-2)
 RoHS Compliant



Pin	A	B
02	2.54	5.64
03	5.08	8.16
04	7.62	10.72
05	10.16	13.30
06	12.70	15.78
07	15.24	18.40
08	17.78	20.80
09	20.32	23.50
10	22.86	26.00
11	25.40	28.50
12	27.94	31.00
13	30.48	33.50
14	32.02	36.00
15	35.56	38.50
16	38.10	41.20
17	40.64	43.60
18	43.18	46.32
20	48.26	51.34

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. Δ		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X \pm 0.35 .XX \pm 0.25 ANG.	Δ B4	Modify Data	HZF	12/06/2018
01937		MEI			Δ B3	Modify Data	HZF	09/09/2011
		CHECKED BY			Δ B2	Modify Data	HZF	12/26/2008
		HZF		Δ B1	Modify Data	HZF	07/21/2008	
		DRAWING BY		Δ B0	NEW RELEASE	BECKY	07/19/2005	
SCALE	NONE	REV.	B4	UNIT	NO. REV.		REVISIONS	CHK DATE
				mm				

