File No.	030HF07217	SHEET	1/1





SPECIFICATION

1 1. General Characteristics
3.0mm Micro Fit 2XXX Plug Black

2 2. Material&Finish
Housing:PA66(UL94V-0),Black

3. Electrical Characteristics
Current Rating:3A AC/DC
Voltage Rating:250V AC/DC
Withstand Voltage:1500V AC/Minute
Insulation Resistance:1000 Megaohms Min.

4. Environmental Characteristics
Temperature Range:-25°C~+85°C

5. RoHS Compliant





2 Dim. A,B Tolerance As Follow:

Pin	A	B
2~8	±0.15	±0.20
10~16	±0.25	±0.30
18~24	±0.35	±0.40

2

Pin	A	B
2	–	3.8
4	3.0	6.8
6	6.0	9.8
8	9.0	12.8
10	12.0	15.8
12	15.0	18.8
14	18.0	21.8
16	21.0	24.8
18	24.0	27.8
20	27.0	30.8
22	30.0	33.8
24	33.0	36.8

4UCON 元化興業股份有限公司 4UCON TECHNOLOGY INC.

DRAWING No. 2	APPROVED BY MEI	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE 2 X. ±0.5 .X ±0.25 .XX ±0.2 .XXX ±0.08
02588	CHECKED BY HZF	
	DRAWING BY CYP	
SCALE NONE	REV. A2	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
2	A2	Modify Data	HZF	06/07/2017
1	A1	Modify Data	HZF	11/30/2009
0	A0	NEW RELEASE		