




SPECIFICATION

Current Rating:1A Max
 Dielectric Withstanding Voltage:500V AC For 1 Minute
 Contact Resistance:30 Milliohms Max
 Insulation Resistance:1000 Megohms Min At DC 500V
 Total Mating Force:8.0 Kgf Max
 Total Unmating Force:4.0 Kgf Min
 Temperature Range:-55°C~+105°C
 RoHS Compliant

No.	A±0.25	B±0.25	C±0.25	D±0.20
15	30.80	25.00	16.33	2.29
26	39.20	33.32	24.66	2.29
44	53.05	47.04	38.38	2.29
62	69.40	63.50	54.84	2.41

5	3B Nut	2	Brass	H4.75*4.75	Nickel Plated
4	Back-Shell	1	Cold Rolled Steel	T=0.40mm	Tin Plated
3	Front-Shell	1	Cold Rolled Steel	T=0.40mm	Tin Plated
2	Contact	15~62	Brass	T=0.20mm	Gold Flashed
1	Housing	2	P.B.T	UL 94V-0	Blue
No.	Part Name	Q'ty	Material	Remarks & Thickness	Finish

4UCON元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.

02760

APPROVED BY

MEI

CHECKED BY

HZF

DRAWING BY

XYH

UNLESS OTHERWISE
 SPECIFIED
 TOLERANCES ARE
 .X ±0.3
 .XX ±0.20
 .XXX ±0.100
 ANG. ±1°

SCALE

NONE

REV.

BO

UNIT
 mm



NO. REV.

BO NEW RELEASE

REVISIONS

HZF

11/13/2008

CHK

DATE