




SPECIFICATION

Current Rating:1A Max.
Dielectric Withstanding Voltage:500V AC
For 1 Minute
Contact Resistance:30 Milliohms Max.
Insulation Resistance:1000 Megohms Min.
At DC 500V
Total Mating Force:8.0 Kgf Max.
Total Unmating Force:4.0 Kgf Min.
Temperature Range:-55°C~+105°C
RoHS Compliant

No.	A±0.25	B±0.25	C±0.25	D±0.20
15	30.80	25.00	16.33	2.29
26	39.20	33.32	24.66	2.29
44	53.05	47.04	38.38	2.29
62	69.40	63.50	54.84	2.41

P/N	Insulator
02756.02765.02772.02776	Blue
02746.02761.02771.02775	Black
02758.02766.02773.02777	White

4	Back-Shell	1	Cold Rolled Steel	T=0.40mm	Tin Plated
3	Front-Shell	1	Cold Rolled Steel	T=0.40mm	Tin Plated
2	Contact	15~62	Brass	T=0.20mm	Gold Flashed
1	Housing	2	P.B.T	UL 94V-0	Black/Blue/White
No.	Part Name	Q'ty	Material	Remarks & Thickness	Finish

4UCON元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.
02774

APPROVED BY
MEI
CHECKED BY
HZF
DRAWING BY
XYH

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE
.X ±0.3
.XX ±0.20
.XXX ±0.100
ANG. ±1°

SCALE NONE

REV. A0

UNIT mm

NO. REV. A0 NEW RELEASE HZF 06/01/2008

REVISIONS CHK DATE