




SPECIFICATION
Current Rating:1A Max.
Dielectric Withstanding Voltage:500V AC
For 1 Minute
Contact Resistance:30 Milliohms Max.
Insulation Resistance:1000 Megohms Min.
At DC 500V
Total Mating Force:8.0 Kgf Max.
Total Unmating Force:4.0 Kgf Min.
Temperature Range:-55°C~+105°C
RoHS Compliant

No.	A±0.25	B±0.25	C±0.25	D±0.20
15	30.80	25.00	16.33	2.29
26	39.20	33.32	24.66	2.29
44	53.05	47.04	38.38	2.29
62	69.40	63.50	54.84	2.41

P/N	Insulator
02756.02765.02772.02776	Blue
02746.02761.02771.02775	Black
02758.02766.02773.02777	White

4	Back-Shell	1	Cold Rolled Steel	T=0.40mm	Tin Plated
3	Front-Shell	1	Cold Rolled Steel	T=0.40mm	Tin Plated
2	Contact	15~62	Brass	T=0.20mm	Gold Flashed
1	Housing	2	P.B.T	UL 94V-0	Black/Blue/White
No.	Part Name	Q'ty	Material	Remarks & Thickness	Finish

4UCON元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No. 02777		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.3 .XX ±0.20 .XXX ±0.100 ANG. ±1°								
		MEI										
		CHECKED BY										
		HZF										
DRAWING BY		XYH										
SCALE	NONE	REV.	A0	UNIT			AO	NEW RELEASE			HZF	06/01/2008
	5		6	mm	7		NO.	REV.	8	REVISIONS	9	0
											CHK	DATE