





SPECIFICATION



Current Rating:1A
Voltage Rating:250V AC
Withstanding Voltage:500V(One Minute)
Contact Resistance:30 Milliohms Max.
Insulation Resistance:1000 Megaohms Min.
At 500V DC
Operating Temperature:-55°C~+105°C
Shell:Steel,Nickel Plated
Insulator:PBT+30%G.F.(UL94V-0),Black
Contact:Brass,Gold Flash On Contact Area,
Tin Plated On Solder Tails,Over Nickel
Z Flake:Steel,Tin Plated
Screw:Steel,Nickel Plated
RoHS Compliant



9&37Pin



15Pin



Pin	A	B	C
09	16.92	24.99	30.81
15	25.25	33.32	39.20
25	38.96	47.04	53.04
37	55.42	63.50	69.40

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.

02843

SCALE

NONE

APPROVED BY

MEI

CHECKED BY

HZF

DRAWING BY

SONG


REV.

C1

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE Δ

.X ± 0.38 .X* $\pm 3^{\circ}$
.XX ± 0.25 .XX* $\pm 1^{\circ}$
.XXX ± 0.10 .XXX* $\pm 0.5^{\circ}$

UNIT
mm



Δ C1

Modify Data

HZF

03/12/2025

Δ C0

NEW RELEASE

HZF

05/25/2022

NO.REV.

REVISIONS

CHK

DATE