

SPECIFICATIONS:

Contact Current Rating: 1 Ampere

Dielectric Withstanding Voltage: AC 500V R.M.S.

Insulation Resistance : 500Megohms Min. At DC 500V





Contact Resistance: 30Milliohms. Max.

Operating Temperature: $-55^{\circ}\text{C} \sim +105^{\circ}\text{C}$



Contact: Brass , Gold Flashed

Insulator: P.B.T. UL94V-0 Rated

Shell: Cold Rolled Steel, Nickel , Tin, Zinc Plated



Recommended P.C.B. Layout



Circuits	A±0.25	B±0.25	C±0.25
09	30.80	25.00	16.92
15	39.20	33.32	25.25
19	44.80	38.86	30.60
23	50.30	44.30	36.10
25	53.05	47.04	38.96
37	69.40	63.50	55.42

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.

02898

APPROVED BY

MEI

CHECKED BY

BECKY

DRAWING BY

TCF

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE

.X ±0.38

.XX ±0.25

ANG.

UNIT

mm



NEW RELEASE

NO. REV.

REVISIONS

CHK

DATE