| File No. | 371 | SHEET | 1 /1 |
|---|---|---|---|

**SPECIFICATIONS**

Current Rating : 1 AMP
Dielectric Withstanding Voltage :
AC 500V For 1 Minute
Contact Resistance : 30 Milliohms Max.
At DC 100mA
Insulator Resistance : 1000Megohms Min.
At DC 500V
Operating Temperature : −55°C To +105°C
Single Contact Insertion Force : 500g Max.
Single Contact Withdrawal Force : 30g Min.
Contact : Brass
Housing : PBT &30% Glass Fiber UL 94V−0






















| Positon | A | B | C | D |
|---|---|---|---|---|
| *9 | 16.92 | 24.99 | 31.16 | 10.16 |
| 15 | 25.50 | 33.32 | 39.42 | 17.78 |
| 25 | 38.96 | 47.04 | 53.34 | 30.48 |
| 37 | 55.45 | 63.50 | 69.68 | 45.72 |

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

| DRAWING No. | APPROVED BY | UNLESS OTHERWISE SPECIFIED TOLERANCES ARE |
|---|---|---|
| 03033 | MEI | .X ±0.1 |
| | CHECKED BY RAN | .XX ±0.05 |
| | DRAWING BY LCH | .XXX |
| SCALE NONE | REV. A | UNIT mm |

| AREA | REVISIONS | CHK | DATE |
|---|---|---|---|
| | | | |