



SPECIFICATION

Current Rating: 1 Amps
 Withstanding Voltage: 500V(One Minute)
 Insulation Resistance: 1000 Megaohms Min. At DC 500V
 Contact Resistance: 30 Milliohms Max.
 Operating Temperature: -40°C~+85°C
 Contact: Brass

Gold Plated On Contact Area,
 Tin Plated On Solder Tails, Over Nickel
 Insulator: PBT+30%G.F.(UL94V-0), White
 Shell: SPCC, Nickel Plated Front, Tin Plated Rear
 RoHS Compliant

Pin	A	B	C	D
09	16.92	24.99	30.81	19.20
15	25.25	33.32	39.20	27.70
25	38.96	47.04	53.04	41.10
37	55.42	63.50	69.40	57.30
50	52.81	61.00	67.00	55.10

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
03202		MEI			
		HZF			
SCALE		DRAWING BY		.X ±0.38 .X* ±3*	
NONE		CYP		.XX ±0.25 .XX* ±1*	
REV.		A0		.XXX ±0.05 .XXX* ±0.5*	
UNIT		mm		UNIT	
REV.		A0		NO. REV.	

NEW RELEASE		HZF		12/07/2016	
REVISIONS		CHK		DATE	