



△ SPECIFICATION

Current Range:
 Non-Switching:100mA 50V DC
 Switching:25mA 24V DC
 Withstanding Voltage:500V AC 50Hz Or
 60Hz For 1 Minute
 Contact Resistance:50 Milliohms Max.(Initial)
 Insulation Resistance:100 Megaohms Min.
 At 500V DC,60s±5s
 Operation Temperature Range:-40°C~+85°C
 Operation Force:9.8N Max.
 Switch Position:Off Type
 RoHS Compliant





Pin	A	B
1	3.90	2.54
2	6.44	5.08
3	8.98	7.62
4	11.52	10.16
5	14.06	12.70
6	16.60	15.24
7	19.14	17.78
8	21.68	20.32
9	24.22	22.86
10	26.76	25.40
12	31.84	27.94



① ② ③ ④ ⑤	⑤	Base	1	PA66,UL94V-0	Black
	④	Terminal	-	Brass	Gold Plated Over Nickel
	③	Contact	-	Copper Alloy	Gold Plated Over Nickel
	②	Cover	1	PBT,UL94V-0	Blue
	①	Actuator	-	PBT,UL94V-0	White
No.		Description	Q'ty	Material	Remark


△	B3	Modify Data	HZF	06/09/2023
△	B2	Modify Data	HZF	07/10/2018
△	B1	Modify Data	HZF	05/12/2016
△	B0	NEW RELEASE	HZF	10/10/2013
NO.	REV.	REVISIONS	CHK	DATE

△ Recommended P.C.B. Layout



DRAWING No.	△
APPROVED BY	MEI
CHECKED BY	HZF
DRAWING BY	CYP
SCALE	NONE
REV.	B3

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
~10 ±0.10
10~ ±0.20
UNIT mm



4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

07242