


SPECIFICATIONS:

SHELL : STEEL MATERIAL, FRONT SHELL NICKEL FINISHED
 BACK SHELL TIN FINISHED
 DIMPLES ON PLUG ONLY

INSULATOR : PBT THERMOPLASTIC, 30% GLASS
 FILLED, UL 94V-0 RATED, BLACK COLOR

CONTACT MATERIAL : BRASS
 CONTACT FINISH : FULL GOLD FLASH
 CONTACT CURRENT RATING : 5.0 AMPS
 CONTACT RESISTANCE : 30 MILLIOHMS MAX.
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.
 INSULATION RESISTANCE : 5000 MEGOHMS MIN.
 TEMPERATURE RATING : -55°C ~ +105°C



No. of Contact	A±0.25	B±0.13	C±0.38	D±0.25	E
09	16.92	24.99	30.81	19.28	11.08
15	25.25	33.32	39.14	27.51	19.39
25	38.96	47.04	53.04	41.28	33.24
37	55.42	63.50	69.32	57.71	49.86

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.
 10913

APPROVED BY MEI
 CHECKED BY BECKY
 DRAWING BY HZF

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 .X
 .XX ±0.13
 ANG. ±2°

SCALE NONE

REV. A0

UNIT mm

NO. REV.

NEW RELEASE
 REVISIONS

MEI
 DATE