








SPECIFICATION
 Voltage Rating:250V
 Current Rating:5 Amp
 Contact Resistance:30 Milliohms Max
 Insulation Resistance:1000 Megaohms Min
 Dielectric Voltage:500V AC R.M.S For 1 Minute
 Temperature Range:-55°C~+105°C
 Housing:PBT+30%G.F(UL94V-0),Black
 Contact:Brass,Gold Plated On Contact Area,Tin
 Plated On Solder Tails,Over Nickel
 Shell:SPCC,Nickel Plated
 Boardlock:SPCC,Tin Plated
 Rivet:Brass,Nickel Plated
 RoHS Compliant



Pin	A	B	C
9	30.81	24.99	16.33
15	39.14	33.32	24.66
25	53.04	47.04	38.38
37	69.32	63.50	54.84

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.

11081

APPROVED BY

MEI

CHECKED BY

HZF


DRAWING BY

CYP

UNLESS OTHERWISE
 SPECIFIED
 TOLERANCES ARE
 X. ±0.50
 XX ±0.30
 XXX ±0.25
 ANG. ±2°

UNIT

mm



NO. REV.

NEW RELEASE

REVISIONS

CHK

03/25/2015

DATE