



△SPECIFICATION

Current Rating:5.0 Amps
 Dielectric Withstanding Voltage:1000V AC For 1 Minute
 Insulator Resistance:5000 Megaohms Min.
 Contact Resistance:30 Milliohms Max.
 Temperature Range:-55°C~+105°C
 Insulator:PBT+30%G.F.(UL94V-0),Black
 Contact:Brass
 Gold Plated 5u" Over All,Over Nickel
 Shell:Steel,Front Nickel Plated After Tin
 RoHS Compliant

| Pin | A±0.25 | B±0.13 | C±0.38 | D±0.25 |
|-----|--------|--------|--------|--------|
| 15 | 16.92 | 24.99 | 30.81 | 19.28 |
| 26 | 25.25 | 33.32 | 39.14 | 27.51 |
| 44 | 38.96 | 47.04 | 53.04 | 41.28 |

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

| | | | | |
|-------------|------|-------------|----|--|
| DRAWING No. | | APPROVED BY | | UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.50 XX ±0.38 XXX ±0.25 XXXX ±0.15 ANG. ±2° |
| 11097 | | MEI | | |
| | | CHECKED BY | | |
| | | HZF | | |
| | | DRAWING BY | | UNIT mm |
| | | CYP | | |
| SCALE | NONE | REV. | A1 | |
| | | | | |

| | | | | |
|------|------|-------------|-----|------------|
| NO. | REV. | REVISIONS | CHK | DATE |
| △ A1 | | Modify Data | HZF | 08/19/2015 |
| △ A0 | | NEW RELEASE | HZF | 12/25/2014 |