




⚠ SPECIFICATION

Current Rating:2.0 Amp
Withstand Voltage:500V AC/DC
Contact Resistance:20 Milliohms Max.
Insulation Resistance:1000 Megaohms Min.
Operation Temperature:−40°C~+105°C
Contact:Phosphor Bronze,Gold Plated Over Nickel
⚠ Insulator:PA9T+30%G.F.(UL94V-0),Black
RoHS Compliant

Recommended P.C.B. Layout(Top Side) ⚠
(PCB Board Tolerance±0.05)

Section A-A ⚠

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No. ⚠

14274

APPROVED BY

EMILY

CHECKED BY

HZF

DRAWING BY

SONG

SCALE

NONE

REV.

A2

UNLESS OTHERWISE

SPECIFIED

TOLERANCES ARE


⚠ .X ±0.40

.XX ±0.25

.XXX ±0.15

ANG. ±3°

UNIT
mm



⚠	A2	Modify Data	HZF	04/24/2014
⚠	A1	Modify Data	HZF	01/04/2010
⚠	A0	NEW RELEASE	BECKY	11/04/2005
NO.	REV.	REVISIONS	CHK	DATE