




Recommended P.C.B. Layout(Top Side)
(PCB Board Tolerance ± 0.05)



△ SPECIFICATION

- Current Rating: 3.0 Amp
Withstand Voltage: 1000V AC/DC
Contact Resistance: 20 Milliohms Max.
Insulation Resistance: 1000 Megaohms Min.
Operation Temperature: -40°C ~ +105°C
Contact: Brass, Gold Plated Over Nickel
Insulator: PBT+30%G.F.(UL94V-0), Black
RoHS Compliant

△△ Series No.	Plastic Q'ty	H	A△
0196	1	11.05	2.30
0196	1	11.05	7.35
0196	1	11.05	12.2
0197	2	13.59	4.85
0197	2	13.59	9.65
0198	3	16.13	2.30
0198	3	16.13	7.10
0199	4	18.67	4.60

DRAWING No.

15421

SCALE

NONE

APPROVED BY

EMILY

CHECKED BY

HZF


DRAWING BY

SONG

REV.

A4

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE
.X ± 0.40
.XX ± 0.25
.XXX ± 0.15
ANG. $\pm 3^\circ$

UNIT
mm

A4

Modify Data

HZF

10/23/2012

A3

Modify Data

HZF

06/07/2012

A2

Modify Data

HZF

02/17/2011

A1

UPDATE DIMENSION

HZF

04/15/2008

A0

NEW RELEASE

SHIN

09/02/2007

NO. REV.

REVISIONS

CHK

DATE

4U CON 元化興業股份有限公司
4U CON TECHNOLOGY INC.