File No. 714JE23801 SHEET 1/1 [2]



[2] Recommended P.C.B. Layout



[2]



[2]



[3] [2]



[3] [2]

[3] SPECIFICATION

1.Material&Finish

[1] Insulator:LCP(UL94V-0),Black
Contact:Brass,Tin Plated
Solder Tabs:Brass,Tin Plated Over Nickel

2.Electrical Characteristics

Current Rating:5A AC,DC
Voltage Rating:250V AC,DC
[2] Contact Resistance:20 Milliohms Max.
Insulation Resistance:1000 Megaohms Min.
Withstand Voltage:1500V AC/Minute

3.Environmental Characteristics

Temperature Range:-25°C~+85°C

4.RoHS Compliant

[3]

Pin	A	B	C
2	--	6.65	4.30
4	3.00	9.65	7.30
6	6.00	12.65	10.30
8	9.00	15.65	13.30
10	12.00	18.65	16.30
12	15.00	21.65	19.30
14	18.00	24.65	22.30
16	21.00	27.65	25.30
18	24.00	30.65	28.30
20	27.00	33.65	31.30
22	30.00	36.65	34.30
24	33.00	39.65	37.30

4UCON 元化興業股份有限公司 4UCON TECHNOLOGY INC.

DRAWING No. [3][1]	18078
APPROVED BY	MEI
CHECKED BY	HZF
DRAWING BY	CYP
SCALE	NONE
REV.	A3
UNIT	mm

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
X. ±0.30
[2] .X ±0.25
.XX ±0.20
.XXX ±0.05
ANG. ±1°

NO.	REV.	REVISIONS	CHK	DATE
[3]	A3	Modify Data	HZF	05/23/2019
[2]	A2	Modify Data	HZF	04/28/2016
[1]	A1	Modify Data	HZF	12/15/2014
[0]	A0	NEW RELEASE	HZF	10/01/2013