File No.	100FC06233	SHEET	1/1

⚠2 SPECIFICATION

Current Rating:1 Amp
Insulation Resistance:5000 Megaohms Min.
Dielectric Withstanding:500V AC
Operating Temperature:−40°C~+105°C
Max. Processing Temperature:
230°C For 30~60 Seconds
(260°C For 10 Seconds)

⚠3 Contact:Phosphor Bronze,Gold Flash Over Nickel
Housing:LCP(UL94V−0),Black
RoHS Compliant



⚠1 Recommended P.C.B. Layout





⚠2



⚠2

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.	APPROVED BY	MEI	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
18463	CHECKED BY	HZF	⚠2 X. ±0.20 .X ±0.15 .XX ±0.10 .XXX ±0.05
	DRAWING BY	YBL	
SCALE NONE	REV.	A3	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
⚠3	A3	Modify Data	HZF	09/26/2013
⚠2	A2	Modify Data	HZF	04/29/2010
⚠1	A1	Modify Data	BECKY	04/11/2006
⚠0	A0	NEW RELEASE	BECKY	04/06/2005