



Recommended P.C.B. Layout(Top View)
(PCB Board Tolerance ± 0.05)




SPECIFICATION

Current Rating:3A

Withstand Voltage:1000V AC Min./Minute
Contact Resistance:20 Milliohms Max.
Insulation Resistance:1000 Megaohms Min.
Operating Temperature:-40°C~+105°C

Insulator:PA9T(UL94V-O),Black
Contact:Brass,Gold Flash Over Nickel
RoHS Compliant



Series no.	Plastic Q'ty	H	A
0196	1	11.00	2.30
0196	1	11.00	7.00
0196	1	11.00	12.30
0197	2	13.50	4.50
0197	2	13.50	9.80
0198	3	16.00	2.00
0198	3	16.00	7.30
0199	4	18.50	4.80

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.

20623

APPROVED BY

EMILY

CHECKED BY

HZF

DRAWING BY

HAO

SCALE

NONE

REV.


A2

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE

.X ±0.30 .X* ±2°
.XX ±0.25 .XX* ±1.5°
.XXX ±0.15 .XXX* ±0.5°

UNIT

mm



NO. REV.

REVISIONS

CHK

DATE

A2

Modify Data

HZF

01/26/2024

A1

Modify Data

HZF

12/20/2023

A0

NEW RELEASE

HZF

05/03/2014