





Recommended P.C.B. Layout(Top View)
(PCB Board Tolerance ± 0.05)



SPECIFICATION

Current Rating:3A
Withstand Voltage:1000V AC Min./Minute
Contact Resistance:20 Milliohms Max.
Insulation Resistance:1000 Megaohms Min.
Operation Temperature:-40°C~+105°C
 Δ Insulator:PA9T(UL94V-0),Black
Contact:Brass,Gold Flash Over Nickel
RoHS Compliant

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.

21468

SCALE

NONE

APPROVED BY

Jason Wu

CHECKED BY

Leo Han

DRAWING BY

Michelle Lee

REV.

A1

UNLESS OTHERWISE SPECIFIED

TOLERANCES ARE Δ

X. ± 0.30 X." $\pm 2^\circ$


.X ± 0.25 .X" $\pm 1.5^\circ$

.XX ± 0.20 .XX" $\pm 1.0^\circ$

.XXX ± 0.15 .XXX" $\pm 0.5^\circ$

UNIT

mm



NO.REV.

REVISIONS

CHK

DATE

Δ A1

Modify Data

HZF

06/27/2024

Δ A0

NEW RELEASE

HZF

06/30/2016