





SPECIFICATION

Current Rating:3 Amp
 Withstand Voltage:500V AC/Minute
 Contact Resistance:20 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Operation Temperature:-40°C~+105°C
 Insulator:PA6T+30%G.F.(UL94V-0),Black
 Contact:Brass,Gold Flash Over Nickel
 RoHS Compliant



Recommended P.C.B. Layout



Pin	A	B	Pin	A	B
02	2.54	5.63	22	53.34	56.43
03	5.08	8.17	23	55.88	58.97
04	7.62	10.71	24	58.42	61.51
05	10.16	13.25	25	60.96	64.05
06	12.70	15.79	26	63.50	66.59
07	15.24	18.33	27	66.04	69.13
08	17.78	20.87	28	68.58	71.67
09	20.32	23.41	29	71.12	74.21
10	22.86	25.95	30	73.66	76.75
11	25.40	28.49	31	76.20	79.29
12	27.94	31.03	32	78.74	81.83
13	30.48	33.57	33	81.28	84.37
14	33.02	36.11	34	83.82	86.91
15	35.56	38.65	35	86.36	89.45
16	38.10	41.19	36	88.90	91.99
17	40.64	43.73	37	91.44	94.53
18	43.18	46.27	38	93.98	97.07
19	45.72	48.81	39	96.52	99.61
20	48.26	51.35	40	99.06	102.15
21	50.80	53.89			

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.

21730

SCALE

NONE

APPROVED BY

MEI

CHECKED BY

HZF

DRAWING BY

CYP

REV.

A0

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE

.X ± 0.30

.XX ± 0.20

UNIT mm



NO. REV.

NEW RELEASE

REVISIONS

CHK

03/30/2017

DATE