



**SPECIFICATION**

Current Rating: 3Amps  
 Withstand Voltage: 1000V AC Min./Minute  
 Contact Resistance: 20 Milliohms Max.  
 Insulation Resistance: 1000 Megohms Min.  
 Operating Temperature:  $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$   
 Insulator: PA6T(UL94V-0), Black  
 Contact: Brass, Gold Flash Over Nickel  
 RoHS Compliant

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
22337		MEI		
		CHECKED BY		
SCALE		REV.		UNIT
NONE		A0		

DRAWING BY		LZX		$X: \pm 0.25$ $X^{\circ}: \pm 2^{\circ}$ $.X: \pm 0.20$ $.X^{\circ}: \pm 1.5^{\circ}$ $.XX: \pm 0.15$ $.XX^{\circ}: \pm 1^{\circ}$ $.XXX: \pm 0.10$ $.XXX^{\circ}: \pm 0.5^{\circ}$
NO. REV.		A0		
NEW RELEASE		HZF		06/20/2022
REVISIONS		CHK		DATE