



SPECIFICATION
 2.54mm Insulating Cable #24AWG
 Current Rating:3.0A
 Voltage Rating:300V AC
 Withstand Voltage:1500V AC/Minute
 Conductor:Copper Wire,Tin Plated
 Recommended P.C.B. Hole:Ø0.95mm
 RoHS Compliant

P/N	Material	Pin	IL	Tp	W	Operation Temperature
22652	NOMEX	6P	76.2	12.7	15.24	-40°C~+105°C
22653	NOMEX	5P	76.2	10.16	12.7	
22654	NOMEX	3P	25.4	5.08	7.62	
22655	NOMEX	5P	50.8	10.16	12.7	
22656	NOMEX	3P	63.5	5.08	7.62	
22657	NOMEX	6P	63.5	12.7	15.24	
22671	NOMEX	4P	25.4	7.62	10.16	
22672	NOMEX	6P	25.4	12.7	15.24	
22673	NOMEX	7P	63.5	15.24	17.78	
22711	NOMEX	14P	152.4	33.02	35.56	
22741	NOMEX	20P	76.2	48.26	50.8	-40°C~+105°C
22674	PET	9P	63.5	20.32	22.86	
22904	PET	6P	50.8	12.7	15.24	
23013	PET	4P	50.8	7.62	10.16	

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. 23110
 APPROVED BY MEI
 CHECKED BY HZF
 DRAWING BY LSM
 UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 .X ±0.38
 .XX ±0.25
 UNIT mm

△	BO	NEW RELEASE	HZF	11/12/2025
NO.	REV.	REVISIONS	CHK	DATE