



**△ SPECIFICATION**  
 Current Rating:1A Max.  
 Withstand Voltage:100V AC For 1 Minute  
 Contact Resistance:30 Milliohms Max.  
 Insulation Resistance:100 Megaohms Min.  
 Total Mating Force:3.57 Kgf Max.  
 Total Umating Force:1.0 Kgf Min.  
 Temperature Range:-30°C~+105°C  
 Housing:LCP+G.F.(UL94V-0),Black  
 Contact:Phosphor Bronze

Contact Finish	Item No.
Gold Flash Over All,Over Nickel	11071
Gold Plated 30u" On Contact Area,Gold Flash On Other Area,Over Nickel	11073

Shell:C2680,Nickel Plated  
 RoHS Compliant

Recommended P.C.B. Layout

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.38 △ X. ±3" .X ±0.20 .X. ±2" .XX ±0.15 .XX. ±1" .XXX ±0.05 .XXX. ±0.5"
11071		CYP		
		HZF		
SCALE		REV.	A2	UNIT
NONE				mm

NO.	REV.	REVISIONS	CHK	DATE
△ A2		Modify Data	HZF	12/27/2018
△ A1		Modify Data	HZF	10/19/2015
△ A0		NEW RELEASE	HZF	04/16/2015