






**SPECIFICATION**  
 ⚠ Current Rating:1A  
 Voltage Rating:250V AC/DC  
 Withstanding Voltage:500V AC/Minute  
 Contact Resistance:20 Milliohms Max.  
 Insulation Resistance:1000 Megaohms Min.  
 Temperature Range:-40°C~+105°C  
 Insulator:PBT+G.F.(UL94V-0),Black  
 ⚠ Contact:Brass,Selective Gold Plated Over Nickel  
 RoHS Compliant



| Pin | A     | B     | C     |
|-----|-------|-------|-------|
| 6   | 12.32 | 6.35  | 5.08  |
| 8   | 14.86 | 8.89  | 7.62  |
| 10  | 17.40 | 11.43 | 10.16 |
| 12  | 19.94 | 13.97 | 12.70 |
| 14  | 22.48 | 16.51 | 15.24 |
| 16  | 25.02 | 19.05 | 17.78 |
| 18  | 27.56 | 21.59 | 20.32 |
| 20  | 30.10 | 24.13 | 22.86 |
| 24  | 35.18 | 29.21 | 27.94 |
| 26  | 37.72 | 31.75 | 30.48 |
| 30  | 42.80 | 36.83 | 35.56 |
| 34  | 47.88 | 41.91 | 40.64 |
| 36  | 50.42 | 44.45 | 43.18 |
| 40  | 55.50 | 49.53 | 48.26 |
| 44  | 60.58 | 54.61 | 53.34 |
| 50  | 68.20 | 62.23 | 60.96 |
| 60  | 80.90 | 74.93 | 73.66 |
| 64  | 85.98 | 80.01 | 78.74 |

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

DRAWING No. 15695  
 APPROVED BY EMILY  
 CHECKED BY HZF  
 DRAWING BY SONG  
 SCALE NONE  
 REV. A3  
 UNLESS OTHERWISE SPECIFIED TOLERANCES ARE  
 X, ±0.3  
 .X ±0.2  
 .XX ±0.1  
 .XXX ±0.05  
 UNIT mm

| NO. | REV. | REVISIONS   | CHK | DATE       |
|-----|------|-------------|-----|------------|
| ⚠   | A3   | Modify Data | HZF | 05/24/2012 |
| ⚠   | A2   | Modify Data | HZF | 10/06/2010 |
| ⚠   | A1   | Modify Data | HZF | 08/13/2010 |
| ⚠   | A0   | NEW RELEASE | HZF | 10/20/2009 |