



SPECIFICATION
 Current Rating:1A AC/DC
 Voltage Rating:250V AC/DC
 Withstanding Voltage:500V AC/Minute
 Contact Resistance:20 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Temperature Range:-40°C~+105°C
 Housing:PBT+G.F.(UL94V-0)
 Contact:Brass,Selective Gold Plated Over Nickel
 RoHS Compliant

Pin	A	B
08	6.0	13.2
10	8.0	15.2
12	10.0	17.2
14	12.0	19.2
16	14.0	21.2
18	16.0	23.2
20	18.0	25.2
22	20.0	27.2
24	22.0	29.2
26	24.0	31.2
28	26.0	33.2
30	28.0	35.2
34	32.0	39.2
36	34.0	41.2
40	38.0	45.2
44	42.0	49.2
50	48.0	55.2
56	54.0	61.2

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. 19563
 APPROVED BY EMILY
 CHECKED BY HZF
 DRAWING BY SONG
 SCALE NONE
 REV. A0

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 X. ±0.30 X.* ±3.0*
 .X ±0.20 .X* ±2.0*
 .XX ±0.15 .XX* ±1.0*
 .XXX ±0.10 .XXX* ±0.5*
 UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△ A0		NEW RELEASE	HZF	06/05/2012