




SPECIFICATION

Current Rating:1A Max.
 Dielectric Withstanding Voltage:500V AC
 For 1 Minute
 Contact Resistance:30 Milliohms Max.
 Insulation Resistance:1000 Megohms Min.
 At DC 500V
 Total Mating Force:8.0 Kgf Max.
 Total Unmating Force:4.0 Kgf Min.
 Temperature Range:-55°C~+105°C
 RoHS Compliant

No.	A±0.25	B±0.25	C±0.25	D±0.20
15	30.80	25.00	16.33	2.29
26	39.20	33.32	24.66	2.29
44	53.05	47.04	38.38	2.29
62	69.40	63.50	54.84	2.41

P/N	Insulator
02756.02765.02772.02776	Blue
02746.02761.02771.02775	Black
02758.02766.02773.02777	White

4	Back-Shell	1	Cold Rolled Steel	T=0.40mm	Tin Plated
3	Front-Shell	1	Cold Rolled Steel	T=0.40mm	Tin Plated
2	Contact	15~62	Brass	T=0.20mm	Gold Flashed
1	Housing	2	P.B.T	UL 94V-0	Black/Blue/White
No.	Part Name	Q'ty	Material	Remarks & Thickness	Finish

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.

02775

APPROVED BY

MEI

CHECKED BY

HZF

DRAWING BY

XYH

UNLESS OTHERWISE
 SPECIFIED
 TOLERANCES ARE
 .X ±0.3
 .XX ±0.20
 .XXX ±0.100
 ANG. ±1°

SCALE NONE

REV. A0

UNIT mm

NO. REV. A0 NEW RELEASE HZF 06/01/2008

REVISIONS CHK DATE