





SPECIFICATION

Current Rating:3A
 Withstand Voltage:1000V AC
 Contact Resistance:20 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Operating Temperature:-40°C~+105°C
 Insulator:PA6T(UL94V-0),Black
 Contact:Brass,Gold Flash Over Nickel
 RoHS Compliant



Series No.	Plastic Q'ty	H	A
0196	1	11.00	2.30
0196	1	11.00	7.00
0196	1	11.00	12.30
0197	2	13.50	4.50
0197	2	13.50	9.80
0198	3	16.00	2.00
0198	3	16.00	7.30
0199	4	18.50	4.80

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.

08418

SCALE NONE

APPROVED BY

EMILY

CHECKED BY

HZF

DRAWING BY

HAO

REV.


A0

UNLESS OTHERWISE
 SPECIFIED
 TOLERANCES ARE

X. ±0.25 X. ±0.25
 .X ±0.20 .X ±0.25
 .XX ±0.15 .XX ±0.15
 .XXX ±0.10 .XXX ±0.15

UNIT

mm



NO. REV.

A0 NEW RELEASE

REVISIONS

CHK

05/03/2014

DATE