



△ SPECIFICATION
 Current Rating: 2A AC/DC
 Voltage Rating: 250V AC/DC
 Operation Temperature: -25°C~+85°C
 Contact Resistance: 20 Milliohms Max.
 Insulation Resistance: 1000 Megaohms Min.
 Terminal: Brass, Tin Plated
 Insulator: PA66+G.F.(UL94V-0)
 RoHS Compliant

Pos.	A	B
4	2.0	6.0
6	4.0	8.0
8	6.0	10.0
10	8.0	12.0
12	10.0	14.0
14	12.0	16.0
16	14.0	18.0
18	16.0	20.0
20	18.0	22.0
22	20.0	24.0
24	22.0	26.0
26	24.0	28.0
28	26.0	30.0
30	28.0	32.0
32	30.0	34.0
34	32.0	36.0
40	38.0	42.0

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. △		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
09726		EMILY		
		CHECKED BY		
		HZF		
		DRAWING BY		.X ±0.35
		HAO		.XX ±0.25
SCALE	NONE	REV.	A3	UNIT
				mm

NO. REV.	REVISIONS	CHK	DATE
△ A3	Modify Data	HZF	03/28/2015
△ A2	Modify Data	HZF	02/23/2010
△ A1	Madify Data	INGRID	03/28/2008
△ A0	NEW RELEASE		