




P.C.Board Hole Dimensions



SPECIFICATIONS

- △ Current Rating: 3A AC, DC
Voltage Rating: 250V AC, DC
Withstanding Voltage: 1500V AC/Minute
Ambient Temperature Range: -40°C To +105°C
Features: 2~20 Circuits Available
Insulator: Nylon 66, UL94V-0
Pin: Brass, Tin Plated
Standard Color: Brown

Circuits	Dimensions	
	A	B
2P	2.54	5.08
3P	5.08	7.62
4P	7.62	10.16
5P	10.16	12.70
6P	12.70	15.24
7P	15.24	17.78
8P	17.78	20.32
9P	20.32	22.86
10P	22.86	25.40
11P	25.40	27.94
12P	27.94	30.48
13P	30.48	33.02
14P	33.02	35.56
15P	35.56	38.10
16P	38.10	40.64
17P	40.64	43.18
18P	43.18	45.72
19P	45.72	48.26
20P	48.26	50.80

△

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.

10589

APPROVED BY

MEI

CHECKED BY

BECKY

DRAWING BY


HZF

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE

.X ±0.25

.XX ±0.15

.XXX ±0.05

UNIT
mm

NO.	REV.	REVISIONS	CHK	DATE
△	A2	Modify Dim	HZF	09/24/2007
△	A2	Update Specifications	HZF	09/24/2007
△	A1	Modify Dim. 29.7 → 27.94	MEI	2004/04/23
△	A0	NEW RELEASE	BECKY	2004/02/26