File No.	432FI24806	SHEET	1/1



Recommended P.C.B. Layout(Top Side) 1
(PCB Board Tolerance±0.05)





2 1 Section B−B



2 1 Section A−A

1 SPECIFICATION

Current Rating:2.0 Amp
Withstand Voltage:500V AC/DC
Contact Resistance:20 Milliohms Max.
Insulation Resistance:1000 Megaohms Min.
Operating Temperature:−40°C~+105°C
2 Insulator:PA9T+30%G.F.(UL94V−0),Black
Contact:Phosphor Bronze,Gold Plated Over Nickel
RoHS Compliant

4UCON 元化興業股份有限公司 4UCON TECHNOLOGY INC.

DRAWING No.	APPROVED BY EMILY	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE 1 .X ±0.40 .XX ±0.25 .XXX ±0.15 ANG. ±3°
12825	CHECKED BY HZF	
	DRAWING BY HAO	
SCALE NONE	REV. A4	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
4	A4	Modify Dim.	HZF	09/24/2015
3	A3	Modify Data	HZF	11/27/2014
2	A2	Modify Data	HZF	10/11/2012
1	A1	Modify Data	HZF	08/18/2011
0	A0	NEW RELEASE	BECKY	11/04/2005