







△ SPECIFICATION
 Current Rating: 3.0 Amp
 Withstand Voltage: 1000V AC/DC
 Contact Resistance: 20 Milliohms Max.
 Insulation Resistance: 1000 Megaohms Min.
 Operation Temperature: -40°C ~ +105°C
 Contact: Brass, Gold Plated Over Nickel
 Insulator: PBT+30%G.F.(UL94V-0), Black
 RoHS Compliant

$\Delta \Delta$	Δ Series No.	Plastic Q'ty	H	A Δ
	0196	1	11.05	2.30
	0196	1	11.05	7.35
	0196	1	11.05	12.2
	0197	2	13.59	4.85
	0197	2	13.59	9.65
	0198	3	16.13	2.30
	0198	3	16.13	7.10
	0199	4	18.67	4.60

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.

15428

SCALE

NONE

APPROVED BY

EMILY

CHECKED BY

HZF

DRAWING BY

SONG

REV.

A4

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE
.X ± 0.40
.XX ± 0.25
.XXX ± 0.15
ANG. $\pm 3^\circ$

UNIT
mm



Δ A4

Modify Data

HZF

10/23/2012

Δ A3

Modify Data

HZF

06/07/2012

Δ A2

Modify Data

HZF

02/17/2011

Δ A1

UPDATE DIMENSION

HZF

04/15/2008

Δ A0

NEW RELEASE

SHIN

09/02/2007

NO. REV.

REVISIONS

CHK

DATE