




Recommended P.C.B. Layout(Top Side)
(PCB Board Tolerance ± 0.05)



△ SPECIFICATION

- Current Rating:3.0 Amp
△ Withstand Voltage:1000V AC/DC
Contact Resistance:20 Milliohms Max.
Insulation Resistance:1000 Megaohms Min.
Operation Temperature:-40°C~+105°C
Contact:Brass,Gold Plated Over Nickel
Insulator:PBT+30%G.F.(UL94V-0),Black
RoHS Compliant

△△ Series No.	Plastic Q'ty	H	A△
0196	1	11.05	2.30
0196	1	11.05	7.35
0196	1	11.05	12.2
0197	2	13.59	4.85
0197	2	13.59	9.65
0198	3	16.13	2.30
0198	3	16.13	7.10
0199	4	18.67	4.60

DRAWING No.

15459

SCALE

NONE

APPROVED BY

EMILY

CHECKED BY

HZF

DRAWING BY

SONG

REV.

A4

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE
.X ± 0.40
.XX ± 0.25
.XXX ± 0.15
ANG. $\pm 3^\circ$

UNIT
mm

△ A4
△ A3
△ A2
△ A1
△ A0
NO. REV.

Modify Data
Modify Data
Modify Data
UPDATE DIMENSION
NEW RELEASE
REVISIONS

HZF
HZF
HZF
HZF
SHIN
CHK
DATE

10/23/2012
06/07/2012
02/17/2011
04/15/2008
09/02/2007

4U CON 元化興業股份有限公司
4U CON TECHNOLOGY INC.