




Recommended P.C.B. Layout



SPECIFICATION

Voltage Rating:250V AC
 Current Rating:15 Amps/Way Max.
 Contact Resistance:20 Milliohms Max.
 Withstanding Voltage:2500V AC(1 Minute),Test Time=60s/1 PCS
 Operation Temperature:-40°C~+105°C
 Soldering Reliability:Test Temperature:250°C±10°C 5s Max.
 Torque:4.0 Kgf.cm/M2.5
 Wire Range:14~24 AWG
 Terminal:Copper Alloy,Tin Plated
 Screw:Steel,Galvanized With Cr3+ Plated
 Wire Guard:Stainless Steel
 Insulator Body(Housing):Polyamide(UL94V-0),Blue
 RoHS Compliant

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.

17582

SCALE NONE

APPROVED BY

MEI

CHECKED BY

HZF

DRAWING BY


HAO

REV.

BO

UNLESS OTHERWISE
 SPECIFIED
 TOLERANCES ARE
 X. ±0.50
 .X ±0.30
 .XX ±0.20
 ANG. ±1°

UNIT
 mm



NO. REV.

REVISIONS

CHK

DATE

BO

NEW RELEASE

HZF

11/05/2015