File No.	689FK20806	SHEET	1/1



Recommended P.C.B. Layout







SPECIFICATION

Voltage Rating:250V AC
Current Rating:15 Amps/Way Max.
Contact Resistance:20 Milliohms Max.
Withstanding Voltage:2500V AC(1 Minute),Test Time=60s/1 PCS
Operation Temperature:−40°C~+105°C
Soldering Reliability:Test Temperature:250°C±10°C 5s Max.
Torque:4.0 Kgf.cm/M2.5
Wire Range:14~24 AWG
Terminal:Copper Alloy,Tin Plated
Screw:Steel,Galvanized With Cr3+ Plated
Wire Guard:Stainless Steel
Insulator Body(Housing):Polyamide(UL94V−0),Blue
RoHS Compliant

4UCON 元化興業股份有限公司 4UCON TECHNOLOGY INC.

DRAWING No.	APPROVED BY MEI	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.50 .X ±0.30 .XX ±0.20 ANG. ±1°
17589	CHECKED BY HZF	
	DRAWING BY HAO	
SCALE NONE	REV. B0	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
0	B0	NEW RELEASE	HZF	11/05/2015