




SPECIFICATION

Current Rating:3.0A
Withstand Voltage:AC 1000V Min./Minute
Contact Resistance:20 Milliohms Max.
Insulation Resistance:1000 Megaohms Min.
Operation Temperature:-40°C~+105°C
Insulator:PBT(UL94V-0),Black
Contact:Brass,Gold Flash Over Nickel
Metal Latch:Zinc Alloy,Nickel Plated
No. Of Contact:08,10,14,16,20,26,30,34,40,44,50,60,64
Contacts Are Tooled Already
RoHS Compliant



4U CON 元化興業股份有限公司
4U CON TECHNOLOGY INC.

DRAWING No.

21774

SCALE

NONE

APPROVED BY

MEI

CHECKED BY

HZF


DRAWING BY

CYP

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE

X.	± 0.25	X.*	$\pm 2^\circ$
.X	± 0.20	.X*	$\pm 1.5^\circ$
.XX	± 0.15	.XX*	$\pm 1^\circ$
.XXX	± 0.10	.XXX*	$\pm 0.5^\circ$

	UNIT
	mm



BO

NEW RELEASE

NO.	REV.
-----	------

REVISIONS

HZF

05/25/2025

CHK

DATE _____