



SPECIFICATION
 Dielectric Withstanding Voltage:500V AC
 Contact Resistance:30 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 At 500V DC
 Operation Temperature:-20°C~+85°C
 Housing:PBT+30%G.F.(UL94V-0),White
 Cover:PA66+30%G.F.(UL94V-0),White
 Contact:Brass,Gold Flash On Contact Area,Tin
 Plated On Solder Tails,Over Nickel
 Shell:SPCC,Nickel Plated Over Copper
 Boardlock:SPCC,Tin Plated
 Rivet:Copper Alloy,Nickel Plated
 Screw:12L14,Nickel Plated
 RoHS Compliant

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.25 .X' ±3" .XX ±0.15 .XX' ±1" .XXX ±0.05 .XXX' ±0.5"
02959		EMILY		
		CHECKED BY		
		HZF		
		DRAWING BY		
		SONG		
SCALE	NONE	REV.	A0	UNIT
				mm

NO.	REV.	REVISIONS	CHK	DATE
△ A0		NEW RELEASE	HZF	02/07/2012