



FEATURES

Half Pitch 1.27mm (.050") Series
 Centronic Type Female Connector For P.C.B
 Stright Dip Solder Type
 Panel Mount Receptacle Assemblies
 Bracket With Latch Block
 Fully EMI/RFI Shielded

MATERIALS

Housing: Plastic Thermoplastic P.B.T,UL 94V-0,Black
 Contact: Phosphor Bronze,Gold Selective Plated
 Front Shell: Steel,Nickel Plated Over Copper
 Latch: Steel,Nickel Plated Over Copper
 Boardlock: Phosphor Bronze,Tn Plated

ELECTRICAL

Current Rating: 1 Amp
 Insulation Resistance: 500 Megohms Min.
 Withstanding Voltage: 500V AC/Min.
 Contact Resistance: 35 Milliohms Max.
 Temperature Range: -55°C~+105°C

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED					
08745		MEI		TOLERANCES ARE					
		CHECKED BY		.XX ±0.13					
		BECKY		.XXX ±0.05					
		DRAWING BY		ANG. ±1°					
		HZF		UNIT		△ BO	NEW RELEASE	BECKY	07/07/2005
SCALE	NONE	REV.	BO	mm	⊕	NO.REV.	REVISIONS	CHK	DATE