


Section A-A



Section B-B

SPECIFICATION

- 1. **Material&Finish**
Material: Phosphor Bronze, Tin Plated
- 2. **Electrical Characteristics**
Current Rating: 5A AC, DC
Voltage Rating: 250V AC, DC
Withstanding Voltage: 1500V AC/Minute
Contact Resistance: 20 Milliohms Max.
- 3. **Environmental Characteristics**
Temperature Range: -25°C ~ +85°C
- 4. **Other**
Applicable Wire: AWG #22~#24
Q'ty: 10000 PCS/Reel
- 5. **RoHS Compliant**

| △△ | P/N | Single Row | Double Rows | C |
|----|-------|------------|-------------|-----------|
| | 01806 | 1X02~1X12 | 2X01~2X05 | 0.58±0.02 |
| | 22900 | | 2X06~2X12 | 0.6±0.02 |

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No. △
01806

APPROVED BY MEI
CHECKED BY HZF
DRAWING BY CYP

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
X. ±0.30
.X ±0.25
.XX ±0.20
.XXX ±0.05
ANG. ±1°

SCALE NONE REV. B2 UNIT mm

| NO. | REV. | REVISIONS | CHK | DATE |
|-----|------|-------------|-----|------------|
| △ | B2 | Modify Data | HZF | 04/23/2025 |
| △ | B1 | Modify Data | HZF | 04/19/2024 |
| △ | B0 | NEW RELEASE | HZF | 12/15/2019 |