

SPECIFICATION

1.

General Characteristics

3.0mm Micro Fit 2XXX Plug Black
2.

Material&Finish

Housing:PA66(UL94V-0),Black
3.

Electrical Characteristics

Current Rating:3A AC/DC

Voltage Rating:250V AC/DC





Withstand Voltage:1500V AC/Minute

Insulation Resistance:1000 Megaohms Min.
4.

Environmental Characteristics

Temperature Range:-25°C~+85°C
5.

RoHS Compliant



Dim. A,B Tolerance As Follow:

Pin	A	B
2~8	±0.15	±0.20
10~16	±0.25	±0.30
18~24	±0.35	±0.40

Pin	A	B
2	-	3.8
4	3.0	6.8
6	6.0	9.8
8	9.0	12.8
10	12.0	15.8
12	15.0	18.8
14	18.0	21.8
16	21.0	24.8
18	24.0	27.8
20	27.0	30.8
22	30.0	33.8
24	33.0	36.8

4UCON

元化興業股份有限公司

4UCON TECHNOLOGY INC.

DRAWING No. 02591

APPROVED BY MEI

CHECKED BY HZF

DRAWING BY CYP

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE

X ±0.5

Y ±0.25

.XX ±0.2

.XXX ±0.08

NO.	REV.	REVISIONS	CHK	DATE
A2		Modify Data	HZF	06/07/2017
A1		Modify Data	HZF	11/30/2009
A0		NEW RELEASE		

SCALE NONE

REV. A2

