


△ 6~12P



Pin	A	B	C	D	E
6	12.32	6.35	5.08	12.12	1.9
8	14.86	8.89	7.62	14.66	1.9
10	17.40	11.43	10.16	17.20	3.8
12	19.94	13.97	12.70	19.74	3.8
14	22.48	16.51	15.24	22.28	3.8
16	25.02	19.05	17.78	24.82	3.8
20	30.10	24.13	22.86	29.90	3.8
24	35.18	29.21	27.94	34.98	3.8
26	37.72	31.75	30.48	37.52	3.8
30	42.80	36.83	35.56	42.60	3.8
34	47.88	41.91	40.64	47.68	3.8
40	55.50	49.53	48.26	55.30	3.8
50	68.20	62.23	60.96	68.00	3.8

4U CON 元化興業股份有限公司
4U CON TECHNOLOGY INC.

DRAWING No.

03709

SCALE	NONE
-------	------

NONE

APPROVED BY

MEI

CHECKED BY

HZF

DRAWING BY

CYP


REV.	
------	--

B3

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE

$\triangle_3 \triangle_2$	X.	± 0.30
	.X	± 0.20
	.XX	± 0.10
	.XXX	± 0.05

UNIT



Δ	B3

3	4 16 21

	LIFE

2010/01/0215

	B3
	B3

3	Modify Data
3	Modify Data

	HZF
	HEF

06/24/2013	
06/25/2013	

2 **B2**

2 | Modify Data

HZF

09/24/2010

1	B1
----------	-----------

1	Del Pin#60,P
---	--------------

	HZF
--	-----

11/28/2007

NO	REV
----	-----

REVISIONS

	DECK
	CHK

	04/04/2000
	DATE