

SPECIFICATION

1.General Characteristics:

0.5mm FPC XXP SMT 90° ZIF Top Contact

2.Material&Finish:

Insulator:PA9T,UL94V-0,Ivory

Slider:PPS,UL94V-0,Black

Terminal:Phosphor Bronze,Tin Plated Over Nickel

Me:Brass,Tin Plated Over Nickel

3.Electrical Characteristics:

Operating Voltage:50V Max.

Current Rating:0.5 Amp Max.

Contact Resistance:20 Milliohms Max.

Insulation Resistance:50 Megaohms Min.

Dielectric Withstanding Voltage:250V AC RMS.

4.Environmental Characteristics:






Operation Temperature:-20°C~+85°C

Processing Temperature:245°C±5°C For 30s

5.Other

Accommodated FFC/FPC Thickness:0.30±0.03mm

6.RoHS Compliant

**4UCON** 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.

08651

APPROVED BY

MEI

CHECKED BY

HZF

DRAWING BY

SONG

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE

.X ±0.35

.XX ±0.20

SCALE

NONE

REV.

B0

UNIT

mm

△ B0
NO. REV.

NEW RELEASE






REVISIONS

HZF

CHK

07/15/2013

DATE



4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.

08651

APPROVED BY

MEI

CHECKED BY

HZF

DRAWING BY

SONG

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE

.X ± 0.35

.XX ± 0.20

SCALE

NONE

REV.

BO

UNIT

mm



NO. REV.

BO NEW RELEASE



REVISIONS

HZF

CHK

07/15/2013

DATE



8		9		0	
File No.	594DG30602	SHEET	3/3		
Pin	A	B	C	D	
4	6.20	7.50	1.50	2.62	J
5	6.70	8.00	2.00	3.12	
6	7.20	8.50	2.50	3.62	
7	7.70	9.00	3.00	4.12	
8	8.20	9.50	3.50	4.62	
9	8.70	10.00	4.00	5.12	
10	9.20	10.50	4.50	5.62	I
11	9.70	11.00	5.00	6.12	
12	10.20	11.50	5.50	6.62	
13	10.70	12.00	6.00	7.12	
14	11.20	12.50	6.50	7.62	
15	11.70	13.00	7.00	8.12	
16	12.20	13.50	7.50	8.62	H
17	12.70	14.00	8.00	9.12	
18	13.20	14.50	8.50	9.62	
19	13.70	15.00	9.00	10.12	
20	14.20	15.50	9.50	10.62	
21	14.70	16.00	10.00	11.12	
22	15.20	16.50	10.50	11.62	G
23	15.70	17.00	11.00	12.12	
24	16.20	17.50	11.50	12.62	
25	16.70	18.00	12.00	13.12	
26	17.20	18.50	12.50	13.62	
27	17.70	19.00	13.00	14.12	
28	18.20	19.50	13.50	14.62	F
29	18.70	20.00	14.00	15.12	
30	19.20	20.50	14.50	15.62	
31	19.70	21.00	15.00	16.12	
32	20.20	21.50	15.50	16.62	
33	20.70	22.00	16.00	17.12	
34	21.20	22.50	16.50	17.62	E
35	21.70	23.00	17.00	18.12	
36	22.20	23.50	17.50	18.62	
37	22.70	24.00	18.00	19.12	
38	23.20	24.50	18.50	19.62	
39	23.70	25.00	19.00	20.12	
40	24.20	25.50	19.50	20.62	D
41	24.70	26.00	20.00	21.12	
42	25.20	26.50	20.50	21.62	
43	25.70	27.00	21.00	22.12	
44	26.20	27.50	21.50	22.62	
45	26.70	28.00	22.00	23.12	
46	27.20	28.50	22.50	23.62	C
47	27.70	29.00	23.00	24.12	
48	28.20	29.50	23.50	24.62	
49	28.70	30.00	24.00	25.12	
50	29.20	30.50	24.50	25.62	
51	29.70	31.00	25.00	26.12	
52	30.20	31.50	25.50	26.62	B
53	30.70	32.00	26.00	27.12	
54	31.20	32.50	26.50	27.62	
55	31.70	33.00	27.00	28.12	
56	32.20	33.50	27.50	28.62	
57	32.70	34.00	28.00	29.12	
58	33.20	34.50	28.50	29.62	
59	33.70	35.00	29.00	30.12	
60	34.20	35.50	29.50	30.62	

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No. 08651		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.35 .XX ±0.20	
		MEI			
		CHECKED BY			
		HZF			
		DRAWING BY			
		SONG			
SCALE	NONE	REV.	BO	UNIT mm	

BO	NEW RELEASE	HZF	07/15/2013
NO. REV.	REVISIONS	CHK	DATE