






SPECIFICATION

Current Rating:16 Amp/Way Max.
 Voltage Rating:300V AC
 Contact Resistance:20 Milliohms Max.
 Withstanding Voltage:2500V AC(1 Minute)
 Test Time=60 Sec./1 PCS
 Operation Temperature:-40°C~+105°C
 Soldering Reliability:Test Temperature=250°C±10°C/
 5 Seconds Max.
 Wire Range:12~26 AWG
 Torque:5.0 Kgf.cm/M3
 Insulator Body(Housing):Polyamide(UL94V-0),Green
 Contact(Metal Housing):Copper Alloy,Nickel Plated
 Wire Guard:Copper Alloy,Tin Plated
 Screw:Steel,Galvanized With Cr3+ Plated
 RoHS Compliant



4UCON

元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. 4/2

09181

SCALE NONE

APPROVED BY

MEI

CHECKED BY

HZF

DRAWING BY


YBL

REV.

A4

UNLESS OTHERWISE
 SPECIFIED
 TOLERANCES ARE
 X. ±0.50
 .X ±0.30
 .XX ±0.20
 ANG. ±1°

UNIT
 mm



NO.

REV.

REVISIONS

CHK

DATE

A4

Modify Data

HZF

08/07/2014

A3

Modify Data

HZF

02/12/2014

A2

Modify Data

HZF

12/16/2011

A1

Modify Data

HZF

06/29/2010

A0

NEW RELEASE

HZF

04/10/2009