




SPECIFICATION


- 1.General Characteristics
3.0mm Micro-Fit 1XXX Receptacle
Black Insulator
- 2.Material&Finish
Insulator:PA66(UL94V-0),Black
- 3.Electrical Characteristics
Current Rating:5A AC/DC
Voltage Rating:250V AC/DC
Withstanding Voltage:1500V AC/Minute
Insulation Resistance:1000 Megaohms Min.
- 4.Environmental Characteristics
Temperature Range:-25°C~+85°C
- 5.RoHS Compliant

Pin	A	B
02	3.0	6.85
03	6.0	9.85
04	9.0	12.85
05	12.0	15.85
06	15.0	18.85
07	18.0	21.85
08	21.0	24.85
09	24.0	27.85
10	27.0	30.85
11	30.0	33.85
12	33.0	36.85

4UCON元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No. 10149		APPROVED BY EMILY	
		CHECKED BY HZF	
		DRAWING BY SONG	
SCALE	NONE	REV.	A1

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
.X	±0.38
.XX	±0.25
ANG.	
UNIT	mm



NO.	REV.	REVISIONS	CHK	DATE
△A1		Modify Data	HZF	08/08/2013
△A0		NEW RELEASE	HZF	05/30/2009