








 SPECIFICATION

Current Rating:3A(22 AWG)
Voltage Rating:250V AC(RMS)/DC
Withstand Voltage:1000V AC For 1 Minute
Contact Resistance:20 Milliohms Max.
Insulation Resistance:1000 Megaohms Min.
Ambient Temperature Range:-25°C~+85°C
Insulator:PA66(UL94V-0),White
Contact:Brass,Tin Plated
RoHS Compliant



Pin	A	B
2	7.48	--
3	9.98	5.00
4	12.48	7.50
5	14.98	10.00
6	17.48	12.50
7	19.98	15.00
8	22.48	17.50
9	24.98	20.00
10	27.48	22.50
11	29.98	25.00
12	32.48	27.50
13	34.98	30.00
14	37.48	32.50
15	39.98	35.00

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No. 

11316

APPROVED BY MEI

CHECKED BY HZF

DRAWING BY CYP

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE
 .X ±0.25
.XX ±0.15
.XXX ±0.08


SCALE

NONE

REV.

A2

UNIT
mm



NO. REV.

REVISIONS

CHK

DATE

 A2	Modify Data	HZF	04/22/2019
 A1	Modify Data	HZF	05/08/2010
 A0	NEW RELEASE		