








△△ SPECIFICATION

Current Rating:3A(22 AWG)
Voltage Rating:250V AC(RMS)/DC
Withstand Voltage:1000V AC For 1 Minute
Contact Resistance:20 Milliohms Max.
Insulation Resistance:1000 Megaohms Min.
Ambient Temperature Range:-25°C~+85°C
Insulator:PA66(UL94V-0),White
Contact:Brass,Tin Plated
RoHS Compliant



△	Pin	A	B
△	2	7.48	--
	3	9.98	5.00
	4	12.48	7.50
	5	14.98	10.00
	6	17.48	12.50
	7	19.98	15.00
	8	22.48	17.50
	9	24.98	20.00
	10	27.48	22.50
	11	29.98	25.00
	12	32.48	27.50
	13	34.98	30.00
	14	37.48	32.50
	15	39.98	35.00

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No. △

11322

SCALE NONE

APPROVED BY MEI

CHECKED BY HZF

DRAWING BY CYP

REV. A2

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
△ .X ±0.25
.XX ±0.15
.XXX ±0.08

UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△	A2	Modify Data	HZF	04/22/2019
△	A1	Modify Data	HZF	05/08/2010
△	A0	NEW RELEASE		