





SPECIFICATION

Current Rating:16 Amp/Way Max.
 Voltage Rating:300V AC
 Contact Resistance:20 Milliohms Max.
 Withstanding Voltage:2500V AC(1 Minute)
 Test Time=60 Sec./1 PCS
 Operation Temperature:-40°C~+105°C
 Soldering Reliability:Test Temperature=250°C±10°C/
 5 Seconds Max.
 Wire Range:12~26 AWG
 Torque:5.0 kgf.cm/M3
 Insulator Body(Housing):Polyamide(UL94V-0),Green
 ⚠Contact(Metal Housing):Copper Alloy,Nickel Plated
 ⚠Wire Guard:Copper Alloy,Tin Plated
 Terminal Screw:Steel,Galvanized With Cr3+ Plated
 RoHS Compliant



4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.

14408

APPROVED BY EMILY

CHECKED BY HZF

DRAWING BY CYP

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 X. ±0.50
 .X ±0.30
 .XX ±0.20
 X° ±1°

SCALE

NONE

REV.

A1

UNIT mm



NO. REV.

REVISIONS

CHK

DATE

⚠ A1 Modify Data HZF 06/01/2015

⚠ A0 NEW RELEASE HZF 06/21/2011