



**SPECIFICATION**

Current Rating: 3.0 Amp  
 Δ Withstand Voltage: 1000V AC/DC  
 Contact Resistance: 20 Milliohms Max.  
 Insulation Resistance: 1000 Megaohms Min.  
 Operation Temperature: -40°C ~ +105°C  
 Contact: Brass, Gold Plated Over Nickel  
 Insulator: PBT+30%G.F.(UL94V-0), Black  
 RoHS Compliant

| Series No. | Plastic Q'ty | H     | A    |
|------------|--------------|-------|------|
| 0196       | 1            | 11.05 | 2.30 |
| 0196       | 1            | 11.05 | 7.35 |
| 0196       | 1            | 11.05 | 12.2 |
| 0197       | 2            | 13.59 | 4.85 |
| 0197       | 2            | 13.59 | 9.65 |
| 0198       | 3            | 16.13 | 2.30 |
| 0198       | 3            | 16.13 | 7.10 |
| 0199       | 4            | 18.67 | 4.60 |

**4UCON** 元化興業股份有限公司  
4UCON TECHNOLOGY INC.

|             |      |             |    |  |
|-------------|------|-------------|----|--|
| DRAWING No. |      | APPROVED BY |    | UNLESS OTHERWISE SPECIFIED TOLERANCES ARE<br>.X ±0.40<br>.XX ±0.25<br>.XXX ±0.15<br>ANG. ±3° |
| 15197       |      | EMILY       |    |  |
|             |      | CHECKED BY  |    |  |
|             |      | HZF         |    |  |
|             |      | DRAWING BY  |    | UNIT mm  |
|             |      | SONG        |    |  |
| SCALE       | NONE | REV.        | B1 | NO. REV.   |
|             |      |             |    |  |

|          |             |     |            |
|----------|-------------|-----|------------|
| Δ B1     | Modify Data | HZF | 10/22/2012 |
| Δ B0     | NEW RELEASE | HZF | 05/23/2012 |
| NO. REV. | REVISIONS   | CHK | DATE       |