

SPECIFICATION

Current Rating:1A Max








Dielectric Withstanding Voltage:500V(AC)
For 1Minute

Contact Resistance:30Milliohms Max

Insulation Resistance:1000Megohms Min
At DC 500V

Temperature Range:-55°C~+105°C

RoHS Compliant



4	Back-Shell	1	Cold Rolled Steel	T=0.40mm	Tin Plated
3	Front-Shell	1	Cold Rolled Steel	T=0.40mm	Tin Plated
2	Contact	15~62	Brass	T=0.20mm	Gold Flashed
1	Housing	1	P.B.T	UL94V-0	White
No.	Name	Q'ty	Material	Remarks&Thickness	Finish

Position	A±0.25	B±0.25	C±0.25	H±0.20
15	30.80	25.00	16.92	2.29
26	39.20	33.32	25.25	2.29
44	53.05	47.04	38.96	2.29
62	69.40	63.50	55.42	2.41

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.

15786

APPROVED BY

MEI

CHECKED BY

HZF

DRAWING BY

HYY

UNLESS OTHERWISE
SPECIFIED

TOLERANCES ARE

.X ±0.3

.XX ±0.20

.XXX ±0.100

ANG. ±1°

SCALE

NONE

REV.

B0

UNIT

mm



NO.

REV.

NEW RELEASE

REVISIONS

HZF

CHK

11/13/2008

DATE