



**△△ SPECIFICATION**  
 Current Rating: 1A  
 Operation Temperature: -55°C~+105°C  
 Insulation Resistance: 1000 Megohms Min.  
 Contact Resistance: 20 Milliohms Max.  
 Dielectric Strength: 500V AC/Minute  
 Housing: PA6T(UL94V-0), Black  
 Contact: Brass, Gold Flash Over Nickel  
 No. Of Contacts: 04~100 Contacts  
 RoHS Compliant

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

|             |    |                |  |  |
|-------------|----|----------------|--|--|
| DRAWING No. |    | APPROVED BY    |  | UNLESS OTHERWISE SPECIFIED TOLERANCES ARE<br>.X ±0.38<br>.XX ±0.25<br>ANG. ±5° |
| 17071       |    | MEI            |  |  |
|             |    | CHECKED BY HZF |  |  |
| SCALE       |    | DRAWING BY     |  | UNIT mm  |
| NONE        |    | CYP            |  |  |
| REV.        | A2 | NO.            |  | ANG.   |
|             |    |                |  | ±5°  |

| NO. | REV. | REVISIONS   | CHK   | DATE       |
|-----|------|-------------|-------|------------|
| △2  | A2   | Modify Data | HZF   | 06/13/2018 |
| △1  | A1   | Modify Data | HZF   | 12/06/2010 |
| △0  | A0   | NEW RELEASE | BECKY | 10/04/2005 |